



SAINT-GOBAIN

UKCA DECLARATION OF PERFORMANCE (DoP)



Trussed rafters

Document Number	Unique number as printed on affixed goods label and delivery paperwork
Identification	As Works Order reference number
Type	Trussed rafter
Intended Use	In Buildings – Use Class 1 & Class 2 BS EN 14250: 2010, Timber structures – Product requirements for pre-fabricated structural members assembled with punched metal plate fasteners
Manufacturer	Saint-Gobain Construction Products UK Limited

Manufacturing Plants:

3 DALCROSS INDUSTRIAL ESTATE
INVERNESS
IV2 7XB
[Cert No. 1224-CPR-0233](#)

9 GRAYS ROAD
GREEN ELMS TRADING ESTATE
UDDINGSTON, G71 6ET
[Cert No. 1244-CPR-0240](#)

WIGAN LANE
DUXBURY, CHORLEY
LANCS, PR7 4BU
[Cert No. 1224-CPR-0232](#)

STATION ROAD, STONEY STANTON
LEICESTERSHIRE
LE9 4LU
[Cert No. 1224-CPR-0235](#)

SALBROOK ROAD
SALFORDS
REDHILL, RH1 5GJ
[Cert No. 1224-CPR-0236](#)

COOKSLAND ROAD
BODMIN
PL31 2RH
[Cert No. 1224-CPR-0229](#)

PINFOLD INDUSTRIAL ESTATE
WOOD LANE
ROTHWELL, LEEDS, LS26 0RP
[Cert No. 1224-CPR-0234](#)

System and assessment of verification of constancy of performance of the construction product as set out in Annex V:

System of Assessment 2 +

Notified Body Element Materials Technology Rotterdam B.V.,
Zekeringstraat 33, 1014 BV, Amsterdam, Netherlands”

Tasks performed by the Notified Body For System 2 +
Initial Assessment of Factory Production Control
Continuous surveillance of Factory Production Control

Certificate of Conformity 2812–CPR- as listed above

Declared Performance


Essential Characteristics	Declared Performance	Harmonised Technical Specification
Mechanical Resistance	Method 3b – BS EN 14250:2010 Initial Type Calculation for load – bearing capacity & stiffness: Pass Strength grade of timber: TR26 Method 2 – BS EN 14250:2010 Initial Type Calculation for load – bearing capacity & stiffness Strength grade of timber: TR26	BS EN 14250:2010 BS 5268-3 BS EN 14250:2010 EN 1995-1-1
Reaction to Fire	D-s2, dO	CWFT – EN 13501 -1
Fire Resistance	NPD	EN 13501 - 2
Release of Dangerous Substances	NPD	
Natural Durability (not treated)	Class 4	EN 350-2
When Preservative Treated	Type : Low pressure vacuum	
Penetration Class	Penetration: NP 1	EN 15228 (BS 8417)
Retention Rates	Retention: 4.5 kg/m3 Use Class 2 Target Biological Agents: Fungi & Insect	EN 15228 (BS 8417)
	Punched metal plates: Pass	EN 14545

The performance of this product is in conformity with the declared performance stated above.

This Declaration of Performance is issued under the sole responsibility of the manufacturing plants identified above.

Signed for and on behalf of the manufacturer by:

Name: Philip Pointon
Function: Quality & Risk Director

Signed: 

Date: 08/10/2024