



SAINT-GOBAIN

CE DECLARATION OF PERFORMANCE (DoP)



Posi Joist

Document Number Unique number as printed on affixed goods label and delivery paperwork

Identification As Works Order reference number

Type Posi Joist

Intended Use In Buildings – Use Class 1 & Class 2
ETA-20/1169 and EAD 130031-00-0304, Timber structures – Product requirements for pre-fabricated structural members assembled with punched metal plate fasteners and metal posi struts

Manufacturer Saint Gobain Construction Products UK t/a Pasquill

Manufacturing Plants:

WIGAN LANE
DUXBURY, CHORLEY
LANCS, PR7 4BU
[Cert No. 2812-CPR-1210](#)

SALBROOK ROAD
SALFORDS
REDHILL, RH1 5GJ
[Cert No. 2812-CPR-1210](#)

COOKSLAND ROAD
BODMIN
PL31 2RH
[Cert No. 2812-CPR-1210](#)

9 GRAYS ROADM ELMS INDUSTRIAL ESTATE
UDDINGSTON,
G71 6ET
[Cert No. 2812-CPR-1210](#)

STATION ROAD
STONE STANTON
LEICESTERSHIRE, LE9 4NA
[Cert No. 2812-CPR-1210](#)

System and assessment of verification of constancy of performance of the construction product as set out in Annex V :

| | |
|---|---|
| System of Assessment | 1 |
| Notified Body | Element Materials Technology Rotterdam B.V., Zekeringstraat 33, 1014 BV, Amsterdam, Netherlands” |
| Tasks performed by the Notified Body | For System 1 Initial Type Testing Initial Assessment of Factory Production Control Continuous surveillance of Factory Production Control |
| Certificate of Conformity | 2812 - CPR - 1210 |

BM Trada performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of constancy of performance on the basis of ETA-20/1169 and EAD 130031-00-0304

Declared Performance

| Essential Characteristics | Declared Performance | Harmonised Technical Specification |
|----------------------------------|--|------------------------------------|
| Reaction to Fire | D-s2, dO | CWFT – EN 13501 -1 |
| Fire Resistance | NPD | EN 13501 - 2 |
| Release of Dangerous Substances | NPD | |
| Natural Durability (not treated) | Class 4 | EN 350-2 |
| When Preservative Treated | Type : Low pressure vacuum | |
| Penetration Class | Penetration : NP 1 | EN 15228 (BS 8417) |
| Retention Rates | Retention : 4.5 kg/m3 Use Class 2 Target Biological Agents : Fungi & Insect | EN 15228 (BS 8417) |
| | Punched metal plates : Pass | EN 14545 |

The performance of this product is in conformity with the declared performance stated above.

This Declaration of Performance is issued under the sole responsibility of the manufacturing plants identified above.

Signed for and on behalf of the manufacturer by:

Name: Philip Pointon

Function: Quality & Risk Director

Signed:  Date: 17/03/2025